

HELPER

Grupuri electrogene de 6 - 7,5 kVA

3000 r.p.m. 50Hz 230V - 400V



- echipament de protectie
- baza ridicata
- schelet usor de ridicat si protejat de rasturnari
- pornire garantata 99%
- alternator stabil de performanta
- baterie de putere mare
- usor de intretinut

Toata aceasta gama include urmatoarele directive:

98/37/CE siguranta masinilor
73/23/CEE voltaj scazut
89/336/CEE compatibilitate electromagnetica
2000/14/CE emisii fonice in mediu pentru echipamente folosite in spatiu deschis

Model	Putere 50Hz				Dimensiuni **A x B x C	Greutate kg	Zgomot db(A)	Rezervor lt
	monofazat 230V		trifazat 400V					
	kVA	KW	kVA	KV	cm			
Benzina								
M6	6	6,6	-	-	570x850x1070	110	55	15
T6	4	4,4	6	6,6	570x850x1070	110	55	15
M8	7,5	8	-	-	570x850x1070	110	55	15
T8	4	4,4	7,5	8	570x850x1070	110	55	15

Dotari

Panou de control

Panou de control automat cu controller digital

- alarma pt depasire viteza, frecventa joasa
- alarma cu led pt nivel scazut ulei, temperatura inalta, eroare la pornire, voltaj scazut al bateriei
- bateria se incarca automat
- protectie diferentiala 300 mA si intrerupator magnetotermic 25A
- intrerupator ATS cu 4 picioare cu 2 contactori gemeni 2 x 30A

Consum la DIN3271A	Motor	Cilindrii	Capacitate	Consum ulei
gr/kWh	companie - tip	Nr	c.c.	% din consum combustibil
313	HONDA GX340	1	337	0,5-1%
313	HONDA GX340	1	337	0,5-1%
313	HONDA GX390	1	389	0,5-1%
313	HONDA GX390	1	389	0,5-1%

Accesorii optionale

- Kit de emisie gaz
- Kit de protectie impotriva ploii