

WELDER

Grupuri electrogene de 2,5 - 7 kVA

3000 r.p.m. 50Hz 230V - 400V



Toata aceasta gama include urmatoarele directive:

98/37/CE siguranta masinilor
73/23/CEE voltaj scazut
89/336/CEE compatibilitate electromagnetica
2000/14/CE emisii fonice in mediu pentru echipamente folosite in spatiu deschis

Model	Putere 50Hz				Dimensiuni **A x B x C	Greutate kg	Zgomot db(A)	Rezervor lt
	monofazat 230V		trifazat 400V					
	kVA	kVA	kVA	kVA	cm			
Benzina								
WB 170 MDC	3	3,3	-	-	720x440x480	78	69	6
WB 220 MDC	5	5,5	-	-	850x500x600	90	71	6,5
WB 220 TDC	3,5	3,8	7,1	6,5	850x500x600	90	80	6,5

Dotari

Panou de control

- panou de control electric cu priza CEE 2P+G, 16A si disjunctori termici IP 44

Consum la DIN3271A	Motor	Cilindrii	Capacitate	Consum ulei
gr/kWh	companie - tip	Nr	c.c.	% din consum combustibil
327	HONDA GX270	1	270	0,5-1%
313	HONDA GX390	1	389	0,5-1%
313	HONDA GX390	1	389	0,5-1%

Accesorii optionale

Toate modelele:

- Extra fire si prelungitoare
- Control portabil cu protectie magnetotermica si diferentiala
- Trailer cu 4 roti (numai pt WB170MDC)