

# SMART EUROMECCSON

Grupuri electrogene de 130 - 1000 kVA

1500 r.p.m. 50Hz 230V - 400V



Toata aceasta gama include urmatoarele directive:

98/37/CE siguranta masinilor

73/23/CEE voltaj scazut

89/336/CEE compatibilitate electromagnetica

2000/14/CE emisii fonice in mediu pentru echipamente folosite in spatiu deschis

Model	Putere 50Hz				Dimensiuni **A x B x C cm	Greutate kg	Autonomie la 75% h	Rezervor lt
	monofazat 230V kVA		trifazat 400V kVA					
<b>Diesel</b>								
WSB 130	-	-	130,2	142,8	3000x1000x1700	1500	6,5	120
WSB 160	-	-	160	176	3000x1000x1700	1750	5	120
WSB 200/I	-	-	202,6	223,6	3500x1150x1700	1950	8	200
WSB 200/D	-	-	207	227	3500x1150x1950	1950	7	200
WSB 250	-	-	250	275	3500x1150x1700	2500	6	200
WSB 300	-	-	300	330	4800x1150x1750	3000	6	230
WSB 330	-	-	327,6	360,3	3600x1400x2100	3000	5,5	230
WSB 380	-	-	377,5	413,7	4800x1400x2000	2600	5,2	250
WSB 400/I	-	-	412,2	453,3	4800x1400x2000	3900	5	250
WSB 450	-	-	462,7	508,7	5000x1400x2150	4500	4	250
WSB 500	-	-	506,3	557	5300x1400x2150	4700	3,5	250
WSB 570	-	-	571,7	631,8	5300x1400x2150	5100	3	250
WSB 650	-	-	638,8	706	6400x1600x2250	6500	3,5	300
WSB 800	-	-	807,1	903,4	6400x1600x2300	7000	2,5	300
WSB 1000	-	-	1022	1125	7770x1900x3150	12700	2	300
WSB 1500 CNT	-	-	1500	1650	9150x2437x3500	17200	1,5	300
WSB 2000 CNT	-	-	2058	2263	10600x2437x3600	22500	1	300

## Dotari

### Panou de control

#### Toate modelele :

- panou de control manual
- izolare IP44
- afisaj: tensiune, curent, frecventa, ore functionare, tensiune baterie, presiune ulei, temperatura apa, nivel combustibil
- alarma la temperatura ridicata si presiune scazuta ulei

Consum la DIN6271A	Motor	Cilindrii	Capacitate	Consum ulei
gr/kWh	companie - tip	Nr	c.c.	% din consum combustibil
212	IVECO NEF67TM2	6	-	0,5-1%
213	IVECO NEF67TM3	6	-	0,5-1%
200	IVECO NEF6TA	6	-	0,5-1%
203	DEUTZ BF6M	6	-	0,5-1%
194	IVECO 78TE	6	-	0,5-1%
194	IVECO 10TE	6	-	0,5-1%
200	VOLVO PENTA TAD941G1	6	-	0,5-1%
198	VOLVO PENTA TAD1241GE	6	-	0,5-1%
194	VOLVO PENTA TAD1242GE	6	-	0,5-1%
194	VOLVO PENTA TAD1640GE	6	-	0,5-1%
198	VOLVO PENTA TAD1641GE	6	-	0,5-1%
200	VOLVO PENTA 1642GE	6	-	0,5-1%
208	PERKINS E18 TAG2	6	-	0,5-1%
197	PERKINS 23TAG3A	6	-	0,5-1%
202	PERKINS TAG2A	6	-	0,5-1%
197	PERKINS TAG2A	8	-	0,5-1%
203	PERKINS TAG2/2A	12	-	0,5-1%

## Accesorii optionale

- Poate fi alimentat cu aer de la o sursa exterioara
- Sistem de alimentare automat
- Baterie 12V, 150mA
- Pregatit pentru remote control
- Trailer pentru facilitarea transportului