

W POWERFUL

Grupuri electrogene de 100 - 2000 kVA

1500 r.p.m. 50Hz 230V - 400V



Toata aceasta gama include urmatoarele directive:

98/37/CE siguranta masinilor

73/23/CEE voltaj scazut

89/336/CEE compatibilitate electromagnetica

2000/14/CE emisii fonice in mediu pentru echipamente folosite in spatiu deschis

Model	Putere 50Hz				Dimensiuni **A x B x C cm	Greutate kg	Autonomie la 75% h	Rezervor lt
	monofazat 230V kVA		trifazat 400V kVA					
Diesel	Pornire electrica							
W 130	-	-	130	114	2400x850x1600	1350	7	120
W 160	-	-	160	176	2500x850x1600	1400	4	120
W 200 D	-	-	207	227	2450x1010x1700	2100	6,5	200
W200 I	-	-	202,6	223,4	2350x800x1450	1650	8	200
W 250	-	-	250	275	2800x1050x1700	2200	6	200
W 300	-	-	300	330	2900x1050x1700	2450	6	230
W 330	-	-	327,6	360,3	2850x1150x1600	2600	5,5	230
W350 V	-	-	350	385	2950x1150x1700	3000	5,5	250
W 350 I	-	-	350	385	3000x1200x1700	2950	5,5	250
W 380	-	-	377,5	413,7	2950x1150x1700	3050	5,2	250
W 400 V	-	-	412,2	453,2	2950x1150x1700	3250	5	250
W 400 I	-	-	412,2	453,2	3000x1200x1700	3250	5	250
W 450	-	-	462,7	508,7	3150x1200x2100	3500	4	250
W 500	-	-	506,3	557	3200x1200x2100	3700	3,5	250
W 570	-	-	571,7	631,8	3300x1200x2100	3800	3	250
W 650	-	-	638,8	706	3850x1700x2100	4950	3,3	300
W 800	-	-	800	880	3800x1750x2300	6200	2	300
W 1000	-	-	1000	1125	5030x1900x2250	7700	2	300
W 1500	-	-	1500	1650	5300x2050x2300	10200	1,5	300
W 2000	-	-	2058	2263	5300x2050x2300	10200	1	300

Dotari

Panou de control

Toate modelele :

- panou de control manual
- izolare IP44
- afisaj: tensiune, curent, frecventa, ore functionare, tensiune baterie, presiune ulei, temperatura apa, nivel combustibil
- alarma la temperatura ridicata si presiune scazuta ulei

Consum la DIN6271A	Motor	Cilindrii	Capacitate	Consum ulei
gr/kWh	companie - tip	Nr	c.c.	% din consum combustibil
212	IVECO NEF67TM2	6	-	0,5-1%
213	IVECO NEF67TM3	6	-	0,5-1%
203	DEUTZ BF6M	6	-	0,5-1%
200	IVECO NEF6TA	6	-	0,5-1%
194	IVECO 78TE2	6	-	0,5-1%
194	IVECO TE1	6	-	0,5-1%
200	VOLVO PENTA TAD941GE	6	-	0,5-1%
196	VOLVO PENTA TAD1240GE	6	-	0,5-1%
203	IVECO 13TE2	6	-	0,5-1%
198	VOLVO PENTA TAD1241GE	6	-	0,5-1%
194	VOLVO PENTA TAD1242GE	6	-	0,5-1%
187	IVECO TE3	6	-	0,5-1%
194	VOLVO PENTA TAD1640GE	6	-	0,5-1%
198	VOLVO PENTA TAD1641GE	6	-	0,5-1%
200	VOLVO PENTA 1642GE	6	-	0,5-1%
208	PERKINS E18 TAG2	6	-	0,5-1%
203	PERKINS 23TAG3A *	6	-	0,5-1%
202	PERKINS TAG2A	6	-	0,5-1%
202	PERKINS TAG2A	8	-	0,5-1%
197	PERKINS TAG2/2A	12	-	0,5-1%

Accesorii optionale

- Poate fi alimentat cu aer de la o sursa exterioara
- Sistem de alimentare automat
- Baterie 12V, 150mA
- Pregatit pentru remote control
- Trailer pentru facilitarea transportului